



# TECHNICAL DATASHEET

Product Name	SKOROIL ALPHA 15W40
Preparation Date	01.11.2019
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** SKOROIL ALPHA 15W40

**Manufacturer:** SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

**Address:** Aydınlı KOSB Mah. Kristal Cad. No:18 İstanbul/TURKEY

**Phone:** 0 (216) 504-0508

**Web:** www.skoroil.com

**E-mail:** info@skoroil.com

## 2. Typical Features

SKOROIL ALPHA 15W-40 is manufactured with high-quality mineral base oils and improved performance additives for diesel-powered cars and light commercial vehicles that can be used safely in all four seasons. Properties

- Excellent viscosity control provides fuel economy and long service life.
- High oxidation stability provides protection until the next oil change.
- It shows high resistance to tearing due to its high viscosity index feature.

Approvals and Specifications;

• API CH-4/CG-4/CF-4 API SL/SJ • ACEA E3/ E5 • MB 228.3 • CUMMINS: CES 20077, 76•, 75, 72, 71  
MAN 3275 • Volvo VDS-2 • RENAULT TURCKS: RD-2 • MTU Level 2 • Deutz DQC-I-05 • MACK: EOM,  
EOM+ • ALLISON: C-4•

Viscosity Class		ALPHA 15W40
Density, @ 15°C g/ml	ASTM D-4052	Max.0.870
Flash Point COC, °C	ASTM D-92	Min.230
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	12.5-16.3
Viscosity Index	ASTM D-2270	Min.120
Pour Point, °C	ASTMD D-97	Max.-27
T.B.N MG/KOH/G	ASTM D-2896	Min.7.5

\* Values may vary from production to production.