



TECHNICAL DATASHEET

Product Name	SKOROIL GEAR 75W80 GL-5
Preparation Date	31.01.2020
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL GEAR 75W80 GL-5

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL GEAR 75W80 GL-5 is a synthetic gear oil that meets API GL-5/GL-4 standards, formulated to meet the performance requirements of harsh conditions. The differential is used in gearboxes where EP gear oils are recommended, including hypoid and worm gears operating under high speed/heavy load, and/or high speed/high torque conditions. It performs very well in axle gears under heavy loads. Improved formulation saves much more fuel than conventional gear oils

. *Properties*

- It has superior pumpability with excellent flowability at low temperatures.
- Thanks to its excellent oil film durability, it has superior lubrication properties
- It does not lose its properties even under heavy working conditions and provides optimum film strength.
- It provides long transmission life with anti-wear and overpressure (EP) performance at all temperatures and under heavy loads.
- Thanks to its very good sealing properties, it reduces maintenance and repair costs.
- Not recommended for automatic, manual, or semi-automatic transmissions where engine oil or automatic transmission fluids are recommended.

Approval and Specifications

- API GL-5/GL-4 • ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B MAN 342M-1 •, MAN 342 M-2 • Scania STO 1:0 • Volvo 1273.12 • DIN 51517 Part 3 • U.S. Steel 224 • AGMA 9005-D94

Viscosity Class		SKOROIL GEAR 75W80 GL-5
Density, @ 15°C g/ml	ASTM D-4052	0.850-0.890
Flash Point COC, °C	ASTM D-92	Min.210
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	8.4-13.5
Viscosity Index	ASTM D-2270	Min.130
Pour Point, °C	ASTM D-97	Max -30

*

Values may vary from production to production