



TECHNICAL DATA SHEET

Substance/Preparation Name	SKOROIL GEAR 80W GL-4
Preparation Date	31.01.2020
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL GEAR 80W GL-4

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL GEAR 80W GL-4 is a special gear oil formulated from mineral-based oils and superior additives obtained from modern refining processes. It has been developed for use in the transmissions of cars and commercial vehicles.

Properties

- *Its formula, developed using state-of-the-art additives, provides maximum protection against wear in the transmission.*
- *It has superior pumpability with its excellent flowability at low temperatures.*
- *Thanks to its excellent oil film durability, it has superior lubrication properties.*
- *Overpressure (EP) resistant, anti-rust, oxidation and anti-foaming properties*

. Approval and Specifications

• API GL-4 • David Brown S1.53.101(E) • U.S. Steel 224 • DIN 51517 Part 3 • AGMA 9005-D94 • ZF TE-ML 02A, 08, 16A, 17A, 19A

Viscosity Class		SKOROIL GEAR 80W GL-4
Density, @ 15°C g/ml	ASTM D-4052	0.850-0.890
Flash Point COC, °C	ASTM D-92	Min.180
Kinematic Viscosity Mm ² /s at 100°C	ASTM D-445	7.0-11.0
Viscosity Index	ASTM D-2270	Min.90
Pour Point, °C	ASTM D-97	Max -27

*

Values may vary from production to production