



TECHNICAL DATA SHEET

Product Name	SKOROIL GEAR 85W140 GL-5
Preparation Date	31.01.2020
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL GEAR 85W140 GL-5

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL GEAR 85W/140 GL-5 is a gear oil formulated with a combination of premium quality mineral base oils and high performance additives. Thanks to its special formula, it provides effective protection against wear that may occur under heavy working conditions. It is safely used in the differentials of many vehicles such as cars, trucks, buses, light duty commercial vehicles, agricultural vehicles and construction machinery.

Properties

- Due to their multi-grade nature, they have a wide temperature operating range, allowing them to perform well at low temperatures.
- It is resistant to overpressure (EP) and has anti-rust, oxidation and foaming properties.
- Thanks to its excellent oil film durability, it has superior lubrication properties.
- Thanks to its multigrade features, it can be used in four seasons.

Approval and Specifications

• API GL-5/GL-4 • ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B MAN 342M-1 •, MAN 342 M-2 • Scania STO 1:0 • Volvo 1273.12 • DIN 51517 Part 3 • U.S. Steel 224 • AGMA 9005-D94

Viscosity Class		SKOROIL GEAR 85W140 GL-5
Density, @ 15°C g/ml	ASTM D-4052	0.860-0.890
Flash Point COC, °C	ASTM D-92	Min.230
Kinematic Viscosity Mm ² /s at 100°C	ASTM D-445	24.5-32.5
Viscosity Index	ASTM D-2270	Min.90
Pour Point, °C	ASTM D-97	Max -15

*

Values may vary from production to production