



TECHNICAL DATA SHEET

Product Name	SKOROIL GEAR SAE 90 GL-1
Preparation Date	31.01.2020
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL GEAR SAE 90 GL-1

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL SAE 90 GL-1 is a gear oil manufactured for use in automotive gearboxes where there is no overpressure operating at normal load and speed and where oil is recommended at API GL-1 level. They are suitable for use in gear units, synchrometer transmissions and differentials that do not require heavy loads because they do not contain excessive pressure additives.

Especially

r • Protects gears from wear when operating in light, non-overpressure conditions.

• Prevents rust and corrosion.

• Prevents foam formation and protects the oil film

. • Does not damage the sealing elements.

Approval and Specifications

• API GL-1

Viscosity Class		SKOROIL SAE 90 GL-1
Density, @ 15°C g/ml	ASTM D-4052	0.870-0.90
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	13.5-18.5
Viscosity Index	ASTM D-2270	Min.90
Pour Point, °C	ASTM D-97	Max -18

*

Values may vary from production to production