



TECHNICAL DATA SHEET

Product Name	SKOROIL MOTORCYCLE 4T 20W50
Preparation Date	31.07.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL MOTORCYCLE 4T 20W50

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.S.

Address: Aydınlı KOSB Mah. Kristal Cad. No :18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL MOTORCYCLE 4T 20W-50 is a premium quality motorcycle oil prepared from well-refined mineral base oils. It is safely used in four-stroke and high-performance, air- or water-cooled motorcycles in all four seasons.

Properties

- Thanks to its high and stable viscosity index, it prevents oil film tearing by keeping the viscosity of the oil under control even under severe conditions.
- Oil life is long thanks to its high resistance to abrasion, rust and corrosion.
- Provides low fuel consumption.
- Provides maximum sustainable engine performance with its special formulation that releases power.

Approval and Specifications • API SJ JASO MA (T903:2011) • JASO MA2 (T903:201)

Viscosity Class		SKOROIL MOTORCYCLE 4T 20W50
Density, @ 15°C g/ml	ASTM D-4052	0,87-0,90
Flash Point COC, °C	ASTM D-92	Min.230
Kinematic Viscosity mm ² /s at 40°C mm ² /s at 100°C	ASTM D-445	16.3-21.9
Viscosity Index	ASTM D-2270	Min.115
Pour Point, °C	ASTM D-97	Max.-24

* Values may vary from production to production.