



TECHNICAL DATA SHEET

| | |
|------------------|-----------------------------|
| Product Name | SKOROIL MOTORCYCLE 4T 10W40 |
| Preparation Date | 31.07.2019 |
| Revision Date | - |
| TDS No | |
| Page Setup | 1 |

1. Product Name and Company Introduction

Product Name: SKOROIL MOTORCYCLE 4T 10W40

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB Mah. Kristal Cad. No:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL MOTORCYCLE 4T 10W-40 is a premium quality synthetic motorcycle oil prepared with advanced technology additives. It is safely used in four-stroke and high-performance, air- or water-cooled motorcycles in all four seasons.

Properties

- Provides excellent engine performance even at high temperatures in air and water cooled engines.
- Thanks to its high and stable viscosity index, it prevents oil film tearing by keeping the viscosity of the oil under control even under severe conditions.
- Oil life is long thanks to its high resistance to abrasion, rust and corrosion.
- Provides low fuel consumption.
- Provides maximum sustainable engine performance with its special formulation that releases power.

Approval and Specifications

- API SL • JASO MA2 (T903:2011) JASO MB (T903:2011) JASO MA (T903:••2011)

| | | |
|--|-------------|-----------------------------|
| Viscosity Class | | SKOROIL MOTORCYCLE 4T 10W40 |
| Density, @ 15°C g/ml | ASTM D-4052 | 0,86-0,90 |
| Flash Point COC, °C | ASTM D-92 | Min.210 |
| Kinematic Viscosity mm ² /s at 40°C mm ² /s at 100°C | ASTM D-445 | 12.5-16.3 |
| Viscosity Index | ASTM D-2270 | Min.140 |
| Pour Point, °C | ASTM D-97 | Max.-27 |

* Values may vary from production to production.