



TECHNICAL DATA SHEET

Product Name	SKOROIL OUTBOARD 2T
Preparation Date	01.11.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL OUTBOARD 2T

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL OUTBOARD 2T, Two-Stroke engine oil, is specially formulated for use in water-cooled two-stroke outboard marine engines.

Properties

- Recommended for water-cooled and outboard motors.
- Excellent corrosion and storage protection.
- Provides exceptional overall engine cleanliness and reduced spark plug pollution.

It is preferable not to mix the Outboard 2T with other oils, as this will not only compromise performance, but can also cause serious damage to the outboard engine.

Approvals and Specifications;

- API TSC 4 ,NMMA TC-W3

Viscosity Class		SKOROIL OUTBOARD 2T
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	7.5-11.5
Flash Point COC, °C	ASTM D-92	Min.200
Viscosity Index	ASTM D-2270	Min.110
Pour Point, °C	ASTMD D-97	Max.-28

* Values may vary from production to production.