



# TECHNICAL DATASHEET

Product Name	SKOROIL 20W50 CF-4
Preparation Date	08.05.2020
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** SKOROIL 20W/50 CF-4/SJ

**Manufacturer:** Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

**Address:** Aydınlı KOSB Mah. Kristal Cad. No:18 İstanbul/TURKEY

**Place of Manufacture Phone No:** 0 (216) 504-0508

**Web:** www.skoroil.com

**E-mail:** info@skoroil.com

## 2. Typical Features

SKOROIL 20W-50 CF-4 is an all-season reliably used engine oil for cars and light commercial vehicles running on diesel fuels, produced with high quality mineral-based base oils and advanced performance additives. It is particularly suitable for passenger cars that operate under difficult conditions and often experience stop-and-go.

Properties

- Its superior fluidity at low temperatures allows for easier start-up.
- Excellent viscosity control ensures fuel economy and long service life
- It has high resistance to tearing due to its high viscosity index.
- Extends oil change intervals even when using high-sulphur fuel.

Approval and Specifications

- API CF-4/SJ • MB 228.1, 229.1 ACEA • A3/B3-04 ACEA • E3-96 Issue 4 • Mack EO-L Plus • MAN 271 • MTU Level 1 • Deutz DQC-I-05 • Volvo VDS

Viscosity Class		SKOROIL 20W50 CF-4
Density 15 °C g/ml	ASTM D-4052	Max.0.890
Flash Point COC, °C	ASTM D-92	Min.230
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	16.3-21.9
Viscosity Index	ASTM D-2270	Min.110
Pour Point, °C	ASTMD D-97	Max.-21

\* Values may vary from production to production.