



# TECHNICAL DATASHEET

Product Name	SKOROIL PREMIUM 5W40 SM/CF
Preparation Date	02.01.2019
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** SKOROIL PREMIUM 5W40 SM/CF

**Manufacturer:** Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

**Address:** Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

**Tel:** 0 (216) 504-0508

**Web:** [www.skoroil.com](http://www.skoroil.com)

**E-mail:** [info@skoroil.com](mailto:info@skoroil.com)

## 2. Typical Features

SKOROIL PREMIUM 5W40 is a fully synthetic motor oil developed by enriching it with synthetic base stocks and qualified additive technology. Recommended for all types of high-performance modern vehicles, passenger cars, multi-point fuel-injected gasoline engines, SUVs and Off-roads. It is recommended not to use any additives with this oil. It is recommended for use in vehicles without diesel particulate filters (DPFs) and gasoline catalytic converters (CATs). Properties;

- Thanks to its synthetic structure, the volatility of the oil is low. This leads to a decrease in fat loss.
- It provides fuel economy with its excellent viscosity control feature.
- It makes it easy to work in the cold with its low temperature flowability.
- It has high resistance to tearing due to its high viscosity index.

Approvals and Specifications; •API SM / API SL • API CF • ACEA A3/B3/B4 • Porsche A40 • Peugeot/Citroën Automobiles B71 2296 • AVTOVAZ (LADA cars) MB-Approval 229.3 • MB-Approval 229.5 Volkswagen • VW50200 Volkswagen • VW50500 Renault RN0700 • Renault RN0710 Opel GM-LL-A-025 • Opel GM-LL-B-025 • BMW Longlife-01•••

Viscosity Class		SKOROIL PREMIUM 5W40 SM/CF
Density, @ 15°C g/ml	ASTM D-4052	0.840-0.880
Flash Point COC, °C	ASTM D-92	Min 210
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	12,5 – 16,3
Viscosity Index	ASTMD 2270	Min.155
Pour Point, °C	ASTM D-97	Max.-35

\* Values may vary from production to production.