

TECHNICAL DATASHEET

| Product Name | SKOROIL ATF | | |
|------------------|-------------|--|--|
| | DEXRON VI | | |
| Preparation Date | 16.06.2023 | | |
| Revision Date | - | | |
| TDS No | | | |
| Page Setup | 1 | | |
| • | | | |

1. Product Name and Company Introduction

Product Name: SKOROIL ATF DEXRON VI

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL ATF DEXRON VI is a superior performance synthetic automatic transmission fluid produced by blending synthetic base stocks and advanced technology additives. It has been developed for use in the new-generation transmissions of passenger cars and light commercial vehicles.

Properties;

- Thanks to its excellent fluidity, it shows high performance at low temperatures.
- Thanks to its high oxidation resistance and thermal stability, it provides superior resistance to aging ensures a long oil change period, and reduces maintenance costs.
- Thanks to its special additives, it extends the life of the transmission by minimizing the wear that may occur in automatic transmissions.
- Thanks to the special additives it contains, it prevents the formation of sediment and does not foam. Provides protection against rust and corrosion.

Approval and Specifications

• General Motors Dexron VI • MB 236.15 , MB 236.16 MB JASO • 1A LV • Honda ATF Type 3.1

| Viscosity Class | | SKOROIL ATF DEXRON VI |
|---------------------------------------|-------------|-----------------------|
| Density 15 °C g/ml | ASTM D-4052 | Max.0.870 |
| Flash Point COC, °C | ASTM D-92 | Min.210 |
| Kinematic Viscosity mm2/s at 100°C | ASTM D-445 | 5.6-9.3 |
| Viscosity Index | ASTM D-2270 | Min.153 |
| Pour Point, °C | ASTMD D-97 | Max40 |

^{*} Values may vary from production to production.