



TECHNICAL DATASHEET

Product Name	SKOROIL TRAC 300 10W30
Preparation Date	18.06.2020
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL TRAC 300 10W30

Manufacturer: Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

Address: Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL TRAC 300 10W/30 is a multi-purpose transmission oil specially developed for use in tractor and agricultural machinery in automatic transmission, ax, hydraulic, wet brake systems, final drive units and power take-offs.

- Provides high performance in power transmission of moving equipment.
- It has excellent low temperature performance and high temperature performance.
- With its friction regulating insertion, it ensures that the brake system operates with high efficiency and quietness.
- Thanks to its high thermal and oxidation stability with the additive packages it contains, it prevents deposit formation and increases working efficiency.

Approvals and Specifications;

• API CF-4/CE/SF API GL-4 F • ORD M2C159-B MF M1139 M1144 M1145 • ACEA E2 • ZF TE-ML 06C • NFE 46803 HV • DIN 51524/3 HVLP • MF M1135 J120C FORD M2C134-D • ZF TE-ML 06E • CASE • MS • • • 1207 • •

Viscosity Class		SKOROIL TRAC 300 10W30
Density, 15 °C g/ml	ASTM D-4052	0,86-0,89
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	9,3-12,5
Viscosity index	ASTM D-2270	Min.110
Pour Point, °C	ASTMD D-97	Max. -27

* Values may vary from production to production