

	<h1>TECHNICAL DATASHEET</h1>	Product Name	SKOROIL XRD TURBO 10W40
		Preparation Date	08.05.2020
		Revision Date	-
		TDS No	
		Page Setup	1

1. Product Name and Company Introduction

Product Name: SKOROIL XRD TURBO 10W40

Manufacturer: Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

Address: Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.skoroil.com

E-mail: info@skoroil.com

2. Typical Features

SKOROIL XRD TURBO 10W40 is an all-season reliably used engine oil for cars and commercial vehicles running on diesel fuels, produced with high quality mineral-based base oils and advanced performance additives.

Properties

- Its superior fluidity at low temperatures allows for easier start-up.
- Excellent viscosity control ensures fuel economy and long service life
- It has high resistance to tearing due to its high viscosity index.
- Extends oil change intervals even when using high-sulphur fuel.

Approval and Specifications

· API CF-4/SJ · MB 228.1, · ACEA A3/ E5 · CUMMINS :CES200077,76,75,72.71,MAN 3275,Volvo · VDS-2
RENAULT TURCKS :RD-2, · MTU Level 2 · Mack EOM EOM+ · ALLISON C-4,CAT ECF1

Viscosity Class		XRD TURBO 10W40
Density 15 °C g/ml	ASTM D-4052	Max.0.880
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	12.5-16.3
Viscosity Index	ASTM D-2270	Min.110
Pour Point, °C	ASTMD D-97	Max.-25

* Values may vary from production to production.