

	<h1>TECHNICAL DATASHEET</h1>	Product Name	SKOROIL XRP TURBO 15W40 CI-4
		Preparation Date	15.11.2021
		Revision Date	-
		TDS No	
		Page	1

## 1. Product Name and Company Introduction

**Product Name:** SKOROIL 15W40 CI-4

**Manufacturer:** Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

**Address:** Aydınlı KOSB Mah. Kristal Cad. No:18 İstanbul/TURKEY

**Tel:** 0 (216) 504-0508

**Web:** [www.skoroil.com](http://www.skoroil.com)

**E-mail:** [info@skoroil.com](mailto:info@skoroil.com)

## 2. Typical Features

SKOROIL XRP TURBO 15W-40 CI-4 is an all-season diesel engine oil developed for use in heavy duty diesel engines. Formulated by adding high-quality performance additives to high-quality base oils.

Properties;

- Thanks to its excellent viscosity, it easily provides first work at low temperatures.
- High oxidation stability provides protection until the next oil change.
- Controls the formation of wear and corrosion and provides maximum protection.
- Thanks to qualified additives, it prevents sediment formation and deposit.
- Prevents oxidation of oil used for a long time.

Approvals and Specifications;

·API CI-4/CH-4/CG-4/CF-4/CF API · SL/SJ ACEA E7-12 (2012) · ACEA A3/B4-12 (2012) · MB-Approval 228.3 MB-Approval 229.1 · MAN M 3275 Volvo VDS-3 · Mack EO-N Mack EO-M PLUS · CAT ECF-2 CUMMINS CES 20076/20077/20078 · CAT ECF-1-a · Renault VI RLD-2 · Deutz DQC-III-10 · Global DHD-1 · Detroit Diesel DDC 93K215 · MTU Type 2 · · · · ·

Viscosity Grade		SKOROIL XRP TURBO 15W40 CI-4
Density 15 °C g/ml	ASTM D-4052	0.87-0.89g/ml
Flash Point COC, °C	ASTM D-92	Min.220 °C
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	12.5-16.3 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	Min.130
Pour Point °C	ASTM D-97	Max.-27

\*The Results may change every production.